

LARGE SCREEN PROJECTION DEVICE

Background of the Invention

Field of the Invention

[0001] This invention relates to a device for large screen projection, with a projection lamp, an image projection plane and an objective lens, the projection lamp directing a cone of light through the image projection plane and through the objective lens. The invention furthermore relates to a projection lamp for the lamp housing of a large screen projector.

Description of Related Art

[0002] A device of the initially mentioned type is part of a large screen projector for movie theaters, training centers, and similar installations and is usually called a "lamp housing" in technical language. The heart of this lamp housing is the projection lamp which is usually a high pressure xenon lamp, due to the high radiant efficiency and the very good color reproduction properties. This is conventionally defined as a high pressure lamp with a glass bulb filled with the rare gas xenon at a high pressure of more than 100 kPa. In projection lamps, xenon is preferred as the filler gas to mercury and sodium vapor to the extent that xenon in the arc, in addition to lines, emits a very intense continuum which in its spectral distribution is similar to daylight, and the light itself, as stated, has very good color reproduction properties. In addition to the glass bulb, the projection lamp also conventionally includes a shell-like reflector in which the glass bulb, aligned according to its optical axis, is held projecting at least partially over the edge of the reflector shell. This reflector reflects the light emitted from the arc in a (round) cone of light, the projection lamp being arranged such that it directs the cone of light through the rectangular image projection plane with the film strip running through there and through the objective lens. The latter is a projection objective lens which is optimized to large screen technology, and thus, is not comparable to an objective lens for ordinary video projection. Therefore, only a truncated pyramid which is rectangular in cross section is used from the cone of light which is circular in cross section.

[0003] One disadvantage of the xenon lamps which are preferred due to the radiant efficiency and color fidelity consists in that, in currently known materials and based on the geometrical configuration (for example, distance of the arc from the reflector) which has been established for known reasons (among others, the temperature load capacity), they have a maximum power of 10,000 W. A power beyond this can only be achieved with cooling; this makes the lamp larger, and thus, more difficult to handle. This maximum power is too little for one design or another of a large screen projection envelope. The trend is toward larger and larger projection areas; this can be recognized, for example, in that each new theater is laid out in the meantime as a "wide screen" theater. For this reason, to illuminate larger and larger image projection areas, therefore, for example, larger and larger movie screens, it is in no way sufficient to simply increase the distance of the projection lamp from the screen; on the one hand, the illuminance of an envelope decreases due to the photometric inverse-square law with the square of its distance from the light source. Thus, the power of the projection lamp when its distance from the projection envelope increases would have to be increased by the square of the increase in distance in order to obtain the same light intensity as before in the projection envelope. This is not possible with current xenon lamps which are limited to 10,000 W. On the other hand, the trend is also toward shorter and shorter theaters with wider and wider image projection areas. The short focal lengths of the projector dictated thereby physically cause a drop of the light intensity to the edge; this leads to unsatisfactory illumination of the image.

[0004] At this point, it is known from 3D technology that two of these known xenon projection lamps next to one another can be used. Figure 1 shows one such arrangement which belongs to the prior art. It consists of two projection lamps 1, 1', each with a shell-shaped reflector 20, 22 in which - aligned according to their optical axes 16, 18 - there is a respective glass bulb 23, 25 which forms the actual light sources 2, 4. Each of these projection lamps 1, 1' directs a partial cone of light 10, 12 through a first prism arrangement 9, 11 which supplies the partial cones of light 10, 12 - each separately and not combined into a common cone of light - to a second prism arrangement 13, 15. Afterwards the partial cones 10, 12 of light pass through the image projection plane 3 and are thrown onto the projection envelope, therefore, for example, a movie screen, by the 3D objective lens 5, in turn, individually and not combined. In this arrangement, the prism arrangements 9, 11 and 13, 15 are used for gradual deflection of the partial cones 10, 12 of

light, which as a result of the distance of the projection lamps 1, 1' from one another, which distance is dictated by the reflectors 20, 22, without the two prism arrangements 9, 11; 13, 15, would strike the image projection plan 3 and especially the objective lens 5 at an overly large angle. Any deflection of the partial cone 10, 12 of light by the prism arrangements 9, 11; 13, 15, of course, is accompanied by a considerable loss of light intensity and color fidelity which must be tolerated in 3D applications. However, it would be desirable here to increase the power of the two projection lamps 1, 1' which is limited to 10,000 W, since, in this way, an increase of the image projection area would be possible.

Summary of the Invention

[0005] A primary object of the invention is to develop a device for large screen projection with a projection lamp which directs a cone of light through an image projection plane and an objective lens such that a clear power increase of the projection lamp can be achieved.

[0006] This object is achieved in a device for large screen projection and by a projection lamp for the lamp housing of a large screen projector of the initially described types in that the projection lamp contains two light sources which are arranged relative to one another such that the envelope of the two partial cones of light which are produced by the light sources, and which feed the (main) cone of light, have at least one common envelope line.

[0007] The approach in accordance with the invention - it is the same in the device for large screen projection as in the projection lamp for the lamp housing of a large screen projector - exploits the fact that the reflector of a projection lamp, in the upper edge area of the reflector shell, reflects only the scattered light which supplied the truncated pyramid-shaped cone of light which can be used for image projection, not at all or only negligibly. The cone of light, based on the given geometrical configuration of a projection lamp, of course, independently of the curvature of the reflector shell, is produced anyway only in a limited inner area of the reflector shell. According to the invention, the device for large screen projection or the projection lamp for the lamp housing of a large screen projector, therefore, contains two light sources, for example, in the form of two conventional xenon high pressure lamps which are arranged relative to one another such that the envelopes of the two individual partial cones of light which are produced by the two light sources are so close

to one another that the two partial cones of light have at least one common envelope line. Here, the designations "envelope of the cone" and "envelope line," terms take from stereometry for describing a cone, are therefore used also to describe the relative position of the two partial cones of light with respect to one another. It is an important element of this invention that the partial cones of the light which are formed by the useful reflected light are so close to one another such that they pass through the image projection plane with the image carrier which passes there as a common (main) cone of light and also penetrate the objective lens as a cone of light. While parallelism of the optical axes of the two light sources due to the geometrical configuration of the light sources, on the one hand, and of the reflectors, on the other, may not be attainable, still an angle as acute as possible between the two optical axes is desirable in order to illuminate the image projection plane (in large format, i.e., with 70 mm film, 36 x 48 mm) adequately and to direct the produced light as much as possible without losses through the objective lens.

[0008] The advantages of the approach in accordance with the invention, on the one hand, lie in a light output roughly 60% higher as compared to the use of a single conventional projection lamp, and on the other hand, in the possibility which accompanies this higher output of being able to illuminate very large image projection envelopes, such as movie screens or the like, with an outstanding light intensity and color intensity.

[0009] Advantageous developments of the invention which apply both to the device for large screen projection and also to the projection lamp for the lamp housing of a large screen projector are described in greater detail below.

[0010] Thus, it is provided, for example, that the optical axes of the two partial cones of light are arranged at an angle of roughly 18° with respect to each other. This value was found by studies of the light distribution on the image projection area using the approach according to the invention.

[0011] It was explained above that the invention, among others, exploits the fact that the cone of light is produced only by one part of the inner reflector shell. This finding is also used to make the two light sources in accordance with the invention with their reflectors such that the two reflectors pass into one another on the common envelope line of the partial cones of light, then the common center line in cross section defining the plane of section of the two reflectors with one another.

[0012] This transition of one (partial) reflector into the other is accomplished preferably by the edges of each of the partial reflectors assigned to the two light sources each being shortened on the side facing one another and the shortened sections being joined to one another. This yields, in turn, a common edge line which defines in cross section a plane of section of the two reflectors with one another.

[0013] One preferred embodiment of the invention is explained in detail using the accompanying drawings.

Brief Description of the Drawings

[0014] Figure 1 is schematic cross-sectional view of a prior art 3D projection arrangement;

[0015] Figure 2 is schematic cross-sectional view of a device for large-screen projection or a projection lamp for the lamp housing of a large screen projector in accordance with the present invention;

[0016] Figure 3A& 3B are light intensity and light area distribution diagrams, respectively, of a light distribution in accordance with the invention;

21 [0017] Figure 4A& 4B are light intensity and light area distribution diagrams, respectively, of a 35 mm film light distribution at the image plane at the image plane; and

[0018] Figure 5A& 5B are light intensity and light area distribution diagrams, respectively, of a 70 mm film light distribution at the image plane.

Detailed Description of the Invention

[0019] The 3D lamp housing as in the prior art was already explained in the introduction. It contains two projection lamps 1, 1' in the form of commercial high pressure xenon lamps which each produce a partial cone 10, 12 of light. These partial cones 10, 12 of light are directed separately through prism arrangements 9, 11; 13, 15 and afterwards through an image projection plane 3 and a 3D objective lens 5. However, in spite of the use of two projection lamps 1, 1' with a maximum 10,000 W power each, light intensity and color intensity cannot be increased beyond the values which can be attained with a single projection lamp. Such a double lamp arrangement is not built for purposes of increasing the power, but simply to be able to project the two images necessary for 3D projection at the same time.

12
[0020] Figure 2 shows a device in accordance with the invention for large screen projection and a projection lamp for the lamp housing of a large screen projector in cross section. The entire device shown, which is also called a "lamp housing" among specialists, contains essentially a projection lamp 1, an image projection plane 3 and an objective lens 5, the projection lamp 1 directing a cone 7 of light through the image projection plane 3 and through the objective lens 5. The projection lamp 1 contains two light sources 2, 4, such as commercially produced high pressure xenon lamps. In these lamps, the light is produced by an arc which is formed in a glass bulb 23, 25 which is filled with xenon gas at a relatively high pressure of more than 100 kPa. A respective reflector 20, 22 is assigned to each of the light sources 2, 4 and they differ from the reflectors of commercial projection lamps in that the edge areas 26, 28 of these reflectors are each shortened on the side facing one another and these shortened sections are connected to one another. The two light sources 2, 4 with their reflectors 20, 22 are positioned relative to one another such that the optical axes 16, 18 of the two reflectors 20, 22 include an angle α of roughly 18° .

13
[0021] The partial cones 10, 12 of light emitted by the light sources 2, 4 by means of the reflectors 20, 22 form that part of the light from the light source 2, 4 which is reflected entirely by the reflectors 20, 22 and which is also used for image projection. This portion of the total light is produced only within an area of the shell-like reflectors 20, 22 which does not include the edge area 26 and 28 at the same time. The portion of the light reflected by these edge areas 26, 28 is specifically scattered light which does not contribute to image projection.

14
[0022] As is apparent from the sectional view in Figure 2, the two partial cones 10, 12 of light are so close to one another that the envelopes of 6, 8 those partial cones 10, 12 of light which are produced by the light sources 2, 4 and which feed the (main) cone 7 of light have a common envelope line 14 in the middle between the two partial cones 10, 12 of light. This common envelope line 14 also defines a plane 24 of section of the two reflectors 20, 22 on which the reflectors 20, 22 pass into one another in the center. This was achieved in this embodiment by the edge areas 26, 28 of the reflectors 20, 22 which contribute nothing to the useful partial cones 10, 12 of light each being shortened on that plane of section 24, therefore on the sides facing one another, and the shortened sections being joined to one another.

[0023] Figures 3A, 3B to 5A, 5B shows three light distribution diagrams 17, 19, 21, in the image projection plane, light distribution diagram 21 being at the image plane 3 in

Fig. 2. Using these three light distribution diagrams of Figures 3A, 3B to 5A, 5B, the initially described problem of inadequate illumination of large image projection areas 27, for example, a movie screen, based in part on the short focal lengths in modern wide screen theaters and partially on the photometric inverse-square law, with uniform light output becomes clear. Figure 3B shows the image projection areas 27 which can be illuminated, of course, into the corners with projected light, and Fig. 3A is a diagram of the corresponding light intensity distribution with uniform power of the light source. Figs. 5A, 5B show light distribution diagrams corresponding to those of Figs. 3A, 3B, but for a image projection 17 of normal size (35 mm film with an image projection plane of 18 x 24 mm) in which the image projection area is designated 27'. Similarly, Figs. 4A, 4B, show an image projection area 27 of a light distribution 19 which is quadrupled in size (large image of 70 mm film with an image projection plane of 36 x 48 mm) and in addition the distribution of the light intensity with uniform power of the light source. The clear flattening of the light intensity curve shows a still relatively high, but, as compared to the example of light distribution 17, clearly reduced light intensity in the center of the area 27, while in the edge areas much lower light intensities can be measured from the start. This highly reduced illuminance of the image projection area 27 is due essentially to the aforementioned photometric inverse-square law and the short focal lengths.

[0024] Finally, light distribution diagram 21 shows the result which can be attained with the device for large screen projection and the projection lamp in accordance with the present invention. The image projection envelope 27 compared to the example of the light distribution 19 is unchanged, and here too the entire image projection envelope into the corners is encompassed by the two partial cones of light. The light distribution diagram 21 in Figs. 3A, 3B show a light and light intensity distribution which is greatly improved relative to the light distribution 19 and which is based on the fact that the cone of light resulting from the two partial cones 10, 12 of light intensifies towards the center of the image and the individual partial cones 10, 12 of light are nearer the right and left image edge than in the single cone of light according to light distributions 17 and 19.

[0025] The double lamp arrangement in accordance with the invention can, of course, also be applied to 3D applications as shown in Figure 1, and then, each of the individual projection lamps could be replaced by the double lamp arrangement of this invention. The

222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1044 1045 1046 1047 1048 1049 1050 1051 1052 1053 1054 1055 1056 1057 1058 1059 1060 1061 1062 1063 1064 1065 1066 1067 1068 1069 1070 1071 1072 1073 1074 1075 1076 1077 1078 1079 1080 1081 1082 1083 1084 1085 1086 1087 1088 1089 1090 1091 1092 1093 1094 1095 1096 1097 1098 1099 1100 1101 1102 1103 1104 1105 1106 1107 1108 1109 1110 1111 1112 1113 1114 1115 1116 1117 1118 1119 1120 1121 1122 1123 1124 1125 1126 1127 1128 1129 1130 1131 1132 1133 1134 1135 1136 1137 1138 1139 1140 1141 1142 1143 1144 1145 1146 1147 1148 1149 1150 1151 1152 1153 1154 1155 1156 1157 1158 1159 1160 1161 1162 1163 1164 1165 1166 1167 1168 1169 1170 1171 1172 1173 1174 1175 1176 1177 1178 1179 1180 1181 1182 1183 1184 1185 1186 1187 1188 1189 1190 1191 1192 1193 1194 1195